

OPERATOR PROTECTION

Thermal Spray Safety Wear

Reference information for protective equipment used around thermal spray and metallizing work.

ORIGINAL TECHNICAL PREVIEW

BU **BALAJI UDYOG**

SAFETY WEARS FOR METALLIZING

Metallizing Helmet
Light weight & comfortable with excellent vision. Supplied from a separate air supply which should be filtered by Helmet Air Conditioner.

Air Breather
This is installed in between compressed air line originating from fitting to the operators helmets. Activated charcoal is contained in the breather unit which separates the oil traces from the compressed air and clean compressed air is fed to the operator's helmet.
PRICE- 2600/-

Helmet Air Conditioner
Air from the air breather is fed to the helmet air conditioner and air is contained before it is fed to the helmet for breathing. It has also a regulator knob so that the operator can regulate the temperature of air fed to the helmet. It is self driven and doesn't need external power.

Ear Muff
Light weight & comfortable. Operator & other personnel close to the spray operation must wear. Protect the operator from noise originating during thermal spray.

Protective Glass
Light weight & comfortable with excellent vision. Operator & other personnel close to the spray operation must wear.

Operator Safety Mask
Ensure clean breathing air at all times. Conforms to current legislation on breathing air quality.

Hand Gloves
These are made of rubber and have anti-static properties. Hand gloves protect the operators' hand against flying abrasive and static charge if any.

5

SAFETY GUIDE

Product document

VERIFIED

Source retained

LIVE LINKS

Website and support


WORLDWIDE

Direct supply

View current information online

Scan for live product details, availability and direct support.

[VISIT BUSPRAY.COM](https://buspray.com)



SAFETY WEARS FOR METALLIZING**Metallizing Helmet**

Light weight & comfortable with excellent vision. Supplied from a separate air supply which should be filtered by Helmet Air Conditioner.

**Air Breather**

This is installed in between compressed air line originating from fitting to the operators helmets. Activated charcoal is contained in the breather unit which separates the oil traces from the compressed air and clean compressed air is fed to the operator's helmet.

**Helmet Air Conditioner**

Air from the air breather is fed to the helmet air conditioner and air is contained before it is fed to the helmet for breathing. It has also a regulator knob so that the operator can regulate the temperature of air fed to the helmet. It is self driven and doesn't need external power.



PRICE- 2600/-

Ear Muff

Light weight & comfortable. Operator & other personnel close to the spray operation must wear. Protect the operator from noise originating during thermal spray.

**Protective Glass**

Light weight & comfortable with excellent vision. Operator & other personnel close to the spray operation must wear.

**Operator Safety Mask**

Ensure clean breathing air at all times. Conforms to current legislation on breathing air quality.

**Hand Gloves**

These are made of rubber and have anti-static properties. Hand gloves protect the operators' hand against flying abrasive and static charge if any.

