

WIRE FLAME SPRAY SYSTEMS

12M and 14M Wire Flame Spray Torches

Product overview for reliable 12M and 14M wire flame spray guns and systems.



SPRAY GUNS

Product document

VERIFIED

Source retained

LIVE LINKS

Website and support

WORLDWIDE

Direct supply

View current information online

Scan for live product details, availability and direct support.

[OPEN PRODUCT ON BUSPRAY.COM](https://www.buspray.com)





FLAME SPRAY TORCH

Features : -

- Excellent finish
- Reliable and efficient
- Long lasting material quality
- High tensile strength
- Corrosion resistant
- High performance
- Easy utilization

BALAJI UDYOG

METAL SPRAY EQUIPMENT

SERVING WHOLE WORLD FROM LAST 13 YEARS

AUTOMATIC SYSTEMS FOR HVOF, PLASMA, FLAME SPRAY, ARC SPRAY



WIRE FLAME SPRAYING SYSTEMS

FLAME SPRAY TORCH-12M FLAME SPRAY TORCH-14M

WIRE FLAME SPRAYING SYSTEMS



WIRE FLAME SPRAY TORCH 12M

WIRE SIZE :	3.17 MM STD. (OTHER SIZES OPTIONAL)
WIRE FEED :	AIR TURBINE)
OUT PUT (SPRAY RATE) :	
ZINC	21.80 KG/HR APPROX.
ALUMINIUM	05.00 KG/HR APPROX.
PURE TIN	22.70 KG/HR APPROX.
BABBIT	22.70 KG/HR APPROX.
MOLYBDENUM	03.40 KG/HR APPROX.
COPPER	10.90 KG/HR APPROX.
CARBON STEEL	05.90 KG/HR APPROX.
PURE NICKEL	04.50 KG/HR APPROX.
GASES USED :	OXYGEN,LPG/PROPANE, ACETYLENE
COMPRESSED AIR :	45 CFM FAD @ 75 PSI
NET WEIGHT :	2.87 KG.

WIRE FLAME SPRAY TORCH 14M

WIRE SIZE :	3.17 MM STD. (OTHER SIZES OPTIONAL)
WIRE FEED :	AIR TURBINE
OUT PUT (SPRAY RATE) :	
ZINC	21.80 KG/HR APPROX.
ALUMINIUM	05.00 KG/HR APPROX.
PURE TIN	22.70 KG/HR APPROX.
BABBIT	22.70 KG/HR APPROX.
MOLYBDENUM	03.40 KG/HR APPROX.
COPPER	10.90 KG/HR APPROX.
CARBON STEEL	05.90 KG/HR APPROX.
PURE NICKEL	04.50 KG/HR APPROX.
GASES USED :	OXYGEN,LPG/PROPANE, ACETYLENE
START-STOP :	HAND TRIGGER
COMPRESSED AIR :	45 CFM FAD @ 75 PSI
NET WEIGHT :	2.65 KG.

